

USED ON: MATERIAL: **P/N SUFFIX DEFINITION** THE CONTENTS OF THIS UNLESS OTHERWISE SPECIFIED DOCUMENT ARE PROPRIETARY -1 CONVERSION COATING DIMENSIONS ARE IN INCHES AND TO NAVITAR, ITS USE IS -2 PAINTING INCLUDE CHEMICALLY APPLIED AUTHORIZED ONLY FOR -3 MARKING **OR PLATED FINISHES RESPONDING TO REQUEST FOR** -R REWORK ROCHESTER, NEW YORK QUOTATION OR PERFORMANCE TOLERANCES AS FOLLOWS OF WORK FOR NAVITAR SCALE: 1:1 DEC. .XXX ±.005 FINISH: DJM 0.0 MOTIC 10X ELWD ICO 0.28 NA & 33.5mm DEC. .XX ±.010 DR: inch 1.0 FRACT. $\pm 1/64$ WD CH: PΒ ANGLES ± 30' CONCENTRICITY .003 TIR APP: PΒ 0.0 25.0 mm REV SIZE 1-62829_OL **BREAK ALL SHARP EDGES** DATE DR: 9/21/2004 .005 MIN. .010 MAX. Α Α CHAMFER ALL THREADS 30" MAX. SURF. ROUGHNESS: $\sqrt[32]{}$ ⊕ DO NOT SCALE DRAWING SHEET 1 OF 1 TO ROOT DIAMETER

OUTLINE