

OUTLINE

USED ON:

MATERIAL:

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES AND
INCLUDE CHEMICALLY APPLIED
OR PLATED FINISHES

P/N SUFFIX DEFINITION

- 1 CONVERSION COATING
- 2 PAINTING
- 3 MARKING
- R REWORK

THE CONTENTS OF THIS
DOCUMENT ARE PROPRIETARY
TO NAVITAR, ITS USE IS
AUTHORIZED ONLY FOR
RESPONDING TO REQUEST FOR
QUOTATION OR PERFORMANCE
OF WORK FOR NAVITAR



TOLERANCES AS FOLLOWS

DEC. .XXX ± .005
DEC. .XX ± .010
FRACT. ± 1/64
ANGLES ± 30'
CONCENTRICITY .003 TIR

SCALE: 1:1



DR: PODLENA

CH:

APP:

DATE DR: 4/4/2002

DO NOT SCALE DRAWING



OBJECTIVE COUPLER-MITUTOYO

FINISH:

BREAK ALL SHARP EDGES
.005 MIN. .010 MAX.
MAX. SURF. ROUGHNESS: $\sqrt{32}$

CHAMFER ALL THREADS 30°
TO ROOT DIAMETER

SIZE	2-50025_OL	REV
A	SHEET 1 OF 1	